

AS

Premium steel door frames for one-piece or welded applications



Power Ready



STC

- △ Rust-inhibiting galvanized steel
- △ Tested to 1,000,000 cycles (Level A)
- △ For interior and exterior use

Die-Mitered Multi-Tab Corner Assembly


7-Gauge Hinge Reinforcing

Water-Based Primer Finish

16-Gauge A60 Galvanized




Complies with ANSI A250.8



Fire-Rated*

- Up to 3hr.
- Singles / Pairs



Hurricane*

- Up to +/- 90psf
- Singles / Pairs

Performance Tested

Independently certified to meet the highest standards in performance for fire, severe weather and endurance testing, all backed by an unmatched factory warranty.

Hardware Compatibility

Engineered to support both steel and wood doors with a variety of custom assemblies including both electrified and mechanical hardware.

Sustainable Design

All frame components are manufactured from environmentally responsible materials using the industry's most advanced manufacturing processes. LEED credits available for recycled content, indoor air quality, and regional sourcing.

Additional Options:

- Custom sizes and hardware configurations
- Special profiles
- Paintable galvanized (unprimed) finish
- Drywall returns (double backbend)
- Welded corners (face, profile, continuous)
- 14-Gauge A60 galvanized steel
- 18-Gauge A60 galvanized steel (3070/6070 only)
- G90 galvanized steel

Applicable Standards:

- ANSI/BHMA A156.115
- ANSI A250.4
- ANSI A250.8
- ASTM A653
- ANSI A250.10
- UL 10B
- UL 10C
- ASTM E2010
- ASTM E2074
- CAN4 S104
- ASTM E90
- ASTM E413

*See specific listings for full details

