

DW16

3-piece knockdown (KD) drywall frames for 1-3/4" doors



Fire-Rated*

- Up to 90min.
- Singles / Pairs



Power Ready



STC

- △ **Efficient post-drywall installation**
- △ **Accelerated schedule friendly**
- △ **Improved jobsite logistics**

**Die-Mitered Multi-Tab
Corner Assembly**

Double Backbend

**Adjustable
Compression Anchor**

**7-Gauge Hinge
Reinforcing**

**Unequal Double
Rabbeted Profile**

**Water-Based Primer
Finish**

**16-Gauge A60
Galvanneal Steel**



**Complies with
ANSI A250.8**

Performance Tested

Independently tested to meet the highest standards in performance for fire and endurance testing, all backed by a one year factory warranty.

Hardware Compatibility

Engineered to support hollow metal and wood doors with a variety of custom assemblies including both electrified and mechanical hardware.

Sustainable Design

All frame components are manufactured from environmentally responsible materials using the industry's most advanced manufacturing processes. LEED credits available for recycled content, indoor air quality, and regional sourcing.

Additional Options:

- Custom sizes and hardware configurations
- Single rabbet profile
- Equal rabbet profile
- Specialty finishes

Applicable Standards:

- ANSI/BHMA A156.115
- ASTM E2074
- ASTM A653
- CAN4 S104
- ANSI A250.10
- ASTM E90
- UL 10B
- ASTM E413
- UL 10C
- ANSI A250.8
- ASTM E2010

*See specific listings for full details

